

GLO LAND CORNER RECORD*

*This form is intended to be used for General Land Office/PLSS corners, but may be used for other survey monuments if a Record of Survey or Monument Removal Permit is not applicable.

GRANTOR/SURVEYOR/PUBLIC OFFICER: This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.

COMPANY OR AGENCY:

ADDRESS:

GRANTEE: PUBLIC

SEAL/SIGNATURE/DATE

LEGAL: $\frac{1}{4}$ _____ $\frac{1}{4}$ _____ SEC: _____ TWP: _____ RGE: _____

CORNER CODE: _____ (From diagram on page 2 of this form)

ADDITIONAL IDENTIFIER : (PLSS corner name, street or plat names, block, lot, etc.)

COUNTY:

WASHINGTON PLANE COORDINATES: N: _____ E: _____

ORDER: _____ ZONE: _____ DATUM (Date of adjustment): _____

BLM Geographic Coordinate Data Base (GCDB) point identifier (optional): _____

CORNER INFORMATION: Discuss the history, evidence found, and perpetuation of the corner. Diagram the references; provide the date of work; and, if applicable, a reference to a map of record and/or the field book/page no. Use the back or additional sheets, if needed.

MARK THE CORNER LOCATION BELOW AND FILL IN THE "CORNER CODE" BLANK ON PAGE 1:
 For corners at the intersection of two lines, the corner code is the alphanumeric coordinate that corresponds to the appropriate intersection of lines.

For corners that are only on one line, the corner code is the line designation and the related line segment; i.e., a corner on line 5 between "B" and "C" is designated BC-5.

For corners that are between lines, the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of Section 18 is designated MN 4-5.

| | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|----|---|---|----|---|---|----|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|---|
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | |
| A | | | | | | | | | | | | | | | | | | | | | | | | | | A |
| B | | | | | | | | | | | | | | | | | | | | | | | | | | B |
| C | | 6 | | | 5 | | | 4 | | | | 3 | | | 2 | | | | 1 | | | | | | | C |
| D | | | | | | | | | | | | | | | | | | | | | | | | | | D |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | E |
| F | | | | | | | | | | | | | | | | | | | | | | | | | | F |
| G | | 7 | | | 8 | | | 9 | | | | 10 | | | 11 | | | | 12 | | | | | | | G |
| H | | | | | | | | | | | | | | | | | | | | | | | | | | H |
| J | | | | | | | | | | | | | | | | | | | | | | | | | | J |
| K | | | | | | | | | | | | | | | | | | | | | | | | | | K |
| L | | 18 | | | 17 | | | 16 | | | | 15 | | | 14 | | | | 13 | | | | | | | L |
| M | | | | | | | | | | | | | | | | | | | | | | | | | | M |
| N | | | | | | | | | | | | | | | | | | | | | | | | | | N |
| O | | | | | | | | | | | | | | | | | | | | | | | | | | O |
| P | | 19 | | | 20 | | | 21 | | | | 22 | | | 23 | | | | 24 | | | | | | | P |
| Q | | | | | | | | | | | | | | | | | | | | | | | | | | Q |
| R | | | | | | | | | | | | | | | | | | | | | | | | | | R |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | S |
| T | | 30 | | | 29 | | | 28 | | | | 27 | | | 26 | | | | 25 | | | | | | | T |
| U | | | | | | | | | | | | | | | | | | | | | | | | | | U |
| V | | | | | | | | | | | | | | | | | | | | | | | | | | V |
| W | | | | | | | | | | | | | | | | | | | | | | | | | | W |
| X | | 31 | | | 32 | | | 33 | | | | 34 | | | 35 | | | | 36 | | | | | | | X |
| Y | | | | | | | | | | | | | | | | | | | | | | | | | | Y |
| Z | | | | | | | | | | | | | | | | | | | | | | | | | | Z |

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT: